MS-3000, High speed magnetic stirrer





DESCRIPTION

MS-3000 is compact magnetic stirrer with stainless steel working surface. Units provide stirring of liquids with rotation speed of magnetic element up to 3000 rpm. Currently it is the highest maximal speed for magnetic stirrers of global producers. Strong magnets hold the driven magnetic element firmly in the magnetic clutch. Stirring is performed without undesirable heating

Enclosures of stirrer **MS-3000** are made of strong steel and painted with powder enamel, which is chemically resistant to acids and alkali

The stirrers are supplied with a cylinder-shape magnetic stirring bar $(6 \times 25 \text{ mm})$ encapsulated in PTFE for universal use. Magnetic stirrers are ideal laboratory instruments for PH-metering, extraction and dialysing with the small quantities of substances. Operation temperature range +4°C to +40°C (from cold rooms to incubators) at maximal relative humidity 80%.

Special colors can be ordered on request.

SPECIFICATION

Speed control range	0-3000 RPM
Stirring volume up to (water)	5 litres
Working surface material	Stainless steel
Max. length of magnetic stirring element (bar)	50 mm
Stirring liquid viscosity	up to 1170 mPa.s
Maximum continuous operation time	24 hrs
Operation in closed laboratory rooms	at ambient temperature from +4°C to +40°C
Working plate size	110×110 mm
Overall dimensions (W×D×H)	120×150×65 mm
Weight	0.8 kg
Input current/power consumption	12 V, 220 mA / 2.6 W
External power supply	Input AC 100-240 V, 50/60 Hz; Output DC 12 V



CAT. NR.

	MS-3000 incl. external power supply unit
BS-010301-AAF	230VAC 50/60Hz Euro plug
BS-010301-AAK	230VAC 50/60Hz UK plug
BS-010301-AAK	230VAC 50/60Hz AU plug
BS-010301-AAK	100VAC 50/60Hz US plug
BS-010301-AAK	120VAC 60Hz US plug
	MS-3000 blue (on request) incl. external power supply unit
BS-010301-ABF	230VAC 50/60Hz Euro plug
BS-010301-AK	IQ OQ document
BS-010301-BK	PQ document

