

SPECIFICATIONS

Temperature setting range	+25°C ... +100°C
Temperature control range	5°C above ambient ... +100°C
Temperature setting resolution	0.1°C
Temperature stability	±0.1°C
Temperature accuracy at +37°C	±0.5°C
Average heating speed from +25°C to +100°C	4°C/min
Temperature uniformity over the block at +37°C	±0.1°C
Temperature uniformity over the block at +100°C	±0.2°C
Temperature calibration coefficient range	0.936...1.063 (± 0.063)
Speed control range	250–1400 rpm
Digital time setting	1 min–96 hrs (1 min increment)
Orbit	2 mm
Display	LCD, 16 x 2 signs
Microprocessor controlled temperature, mixing speed and operation time	+
Maximum continuous operation time	168 h
Overall dimensions (W×D×H)	220x240x90 mm
Weight	3.7 kg
Input current/power consumption	12 V, 3.5 A / 42 W
External power supply	Input AC 100–240 V; 50/60 Hz; Output DC 12 V

ACCESSORIES



SC-18
BS-010120-AK
block

20 × 0.5 ml + 12 × 1.5 ml
microtubes



SC-18/02
BS-010120-CK
block

20 × 0.2 ml microtubes + 12 ×
1.5 ml microtubes



SC-24N
BS-010120-GK
block

24 x 1.5 ml microtubes



SC-24
BS-010120-EK
block

24 × 2 ml microtubes



SC-96A
BS-010120-FK
block

96-well unskirted or semi-
skirted microplate (0.2 ml) for
PCR