

# MSV-3500, Multi Speed Vortex

Basic Plus  
 Product Class

## DESCRIPTION

Multi Speed Vortex **MSV-3500** is designed for soft or intensive mixing of reagents in different size and type plastic tubes (0.2 to 50 ml).

It is designed for operation in life science laboratories working in the fields of biochemistry, cell and molecular biology.

Unit has four types of interchangeable platforms: for Eppendorf type microtest tubes, 10/15/50 ml tubes (diameter 12/16/30 mm). Platforms can be ordered separately or as one set with **MSV-3500**.

Speed and time are under microprocessor control. LCD display indicates two lines of values: the set and actual values of speed and time.

Unit provides high maximum speed of platform rotation efficiently mixing microvolumes (less than 5 µl) of samples.



## SPECIFICATIONS

Speed control range	300–3,500* rpm * Maximum speed depends on load
Digital time setting	0–60 min / non-stop
Maximum continuous operation time	8 hrs
Display	LCD, 2 x 16 signs
Maximum load	0.2 kg
Orbit	4 mm
Overall dimensions (W×D×H)	180x170x145 mm
Weight	2.6 kg
Input current/power consumption	12 V, 1 A / 12 W
External power supply	Input AC 100–240 V; 50/60 Hz; Output DC 12 V

## CAT. NUMBER

<b>With all 4 platforms included</b>	With all 4 platforms included
BS-010210-TAH	230VAC 50/60Hz Euro plug
BS-010210-TAK	230VAC 50/60Hz UK plug, 230VAC 50/60Hz AU plug, 100VAC 50/60Hz US plug, 120VAC 60Hz US plug
<b>Without platform</b>	Without platform
BS-010210-AAH	230VAC 50/60Hz Euro plug
BS-010210-AAK	230VAC 50/60Hz UK plug, 230VAC 50/60Hz AU plug, 120VAC 60Hz US plug
BS-010210-IK	IQ OQ document
BS-010210-JK	PQ document



SV-16/8  
BS-010210-CK  
platform

16/8/8 sockets for 1.5/0.5/0.2 ml microtest tubes (Ø 11/8/6 mm).



SV-10/10  
BS-010210-BK  
platform

10 sockets for 10 ml (Ø 12 mm) tubes.



SV-8/15  
BS-010210-DK  
platform

8 sockets for 15 ml (Ø 16 mm) tubes



SV-4/30  
BS-010210-AK  
platform

4 sockets for 50 ml (Ø 30 mm) tubes